

RM Speedy Rain 32/90

Nozzle	Pressure		Flow Capacity	Throw Radius	Irrigated Strip			Rewind Speed (metres/hour)					
	At Machine	At Sprinkler			Throw Diameter	Suggested	10	15	20	25	30		
	mm	bar					bar	ltr/sec	m3/hr	mtr	mtr	mtr	Rewinding Time In Hours
								85%	Water Application (mm)				
6 **	2	1.5	0.47	1.68	13	26	22.1	9.0	6.0	4.5	3.6	3.0	
	2.7	2	0.53	1.92	14.5	29	24.7	7.6	5.1	3.8	3.0	2.5	
	5.2	4	0.75	2.7	17.5	35	29.8	7.8	5.2	3.9	3.1	2.6	
7	2.4	1.5	0.62	2.22	14	28	23.8	9.1	6.1	4.5	3.6	3.0	
	3.1	2	0.7	2.52	15	30	25.5	9.3	6.2	4.7	3.7	3.1	
	6.1	4	1.0	3.6	18.5	37	31.5	9.9	6.6	4.9	4.0	3.3	
								11.4	7.6	5.7	4.6	3.8	

** Standard Nozzle in Sprinkler

Amount of water exhausted from piston to complete each cycle = 451 litres

Javelin Irrigation Systems Ltd
 The Pump House, Belvoir Way, Fairfield Industrial Estate, Louth, Lincs, LN11 0YA
 Tel 01507 607175
 Fax 01507 607521
 Email sales@javelinirrigation.co.uk
 Web www.javelinirrigation.co.uk

These figures are for guidance purposes only